MITSUBISHI ELECTRIC
ELEVATORS & ESCALATORS

IDH-H-L2 Hydraulic Service Elevators

REVERSE ENTRANCE HOLELESS ELEVATORS
STANDARD SPEEDS: 100 FPM AND 125 FPM

Plan View of Handed Two Speed

LEFT HAND SHOWN - RIGHT HAND AVAILABLE

Plan View of Elevator Pit Condition

Composite Hoistway Section

HOLELESS AND SEMI-HOLELESS HOISTWAY DIMENSIONS							
CAPACITY (LBS.)	HOISTWAY		PLATFORM		CAR INSIDE CLEAR		ENTRANCE
	Width	Depth	Width	Depth	Width	Depth	Width
4000	7' - 8"	10' - 2"	6' - 0"	8' - 11"	5' - 8"	7' - 4 ½"	4' - 0"
4500	7' - 8"	10' - 8"	6' - 0"	9' - 5"	5' - 8"	7' - 10"	4' - 0"
5000	7' - 8"	11' - 3"	6' - 0"	10' - 0"	5' - 8"	8' - 5 ½"	4' - 0"
5000	8' - 5"	11' - 3"	6' - 4"	10' - 0"	6' - 0"	8' - 5 ½"	4' - 6"

NOTES:

1. Complies with ASME A17.1 code. Confirm dimensions comply with local codes and standards.
2. Provide min. 4" wide divider beam between adjacent hoistways for rail support.
3. Cab can be provided in most finishes, including decorative panels or textured stainless steel.
4. Two speed center open entrances are not shown, but are also available.
5. Provide hoisting beam capable of holding 5000 lb. load. Remove after installation if required.

Quality in Motion