

Holeless Single Stage Overhead Dimensions

NOTE:

- 1 For freight car with bi-parting entrance, check with Mitsubishi Sales
- 2 For pit pockets option, check with Mitsubishi Sales
- 3 The min. O.H is calculated based on 6" runby (where speed = 150 FPM) and with car top guard rails.

Capacity (lbs.) 2100, 2500, 3000, 3500				
Pit depth	Cab height	Rise	Min O.H.	
4'-0"	8 ft	< 12'-0"	12'-6"	
		12'-6"	12'-10"	
		13'-0"	13'-4"	
		13'-6"	13'-10"	
		14'-0"	14'-4"	
		14'-6"	14'-10"	
		15'-0"	15'-4"	
		15'-6"	15'-10"	
		16'-0"	16'-4"	
		16'-6"	16'-10"	
		17'-0"	17'-4"	
	
	9 ft	< 12'-0"	13'-6"	
		12'-6"	13'-6"	
		13'-0"	13'-6"	
		13'-6"	13'-10"	
		14'-0"	14'-4"	
		14'-6"	14'-10"	
		15'-0"	15'-4"	
		15'-6"	15'-10"	
		16'-0"	16'-4"	
		16'-6"	16'-10"	
		17'-0"	17'-4"	
	
	10 ft	< 12'-0"	14'-6"	
		12'-6"	14'-6"	
		13'-0"	14'-6"	
		13'-6"	14'-6"	
		14'-0"	14'-6"	
		14'-6"	14'-10"	
		15'-0"	15'-4"	
		15'-6"	15'-10"	
		16'-0"	16'-4"	
		16'-6"	16'-10"	
		17'-0"	17'-4"	
	

Capacity (lbs.) 4000, 4500, 5000					
Pit depth	Cab height	Rise	Min O.H.		
4'-0"	8 ft	< 11'-8"	12'-6"		
		12'-0"	12'-10"		
		12'-6"	13'-4"		
		13'-0"	13'-10"		
		13'-6"	14'-4"		
		14'-0"	14'-10"		
		14'-6"	15'-4"		
		15'-0"	15'-10"		
		15'-6"	16'-4"		
		16'-0"	16'-10"		
		16'-6"	17'-4"		
	
	9 ft	< 12'-0"	13'-6"		
		12'-6"	13'-6"		
		13'-0"	13'-10"		
		13'-6"	14'-4"		
		14'-0"	14'-10"		
		14'-6"	15'-4"		
		15'-0"	15'-10"		
		15'-6"	16'-4"		
		16'-0"	16'-10"		
		16'-6"	17'-4"		
	
		10 ft	< 12'-0"	14'-6"	
	12'-6"		14'-6"		
	13'-0"		14'-6"		
	13'-6"		14'-6"		
	14'-0"		14'-10"		
	14'-6"		15'-4"		
	15'-0"		15'-10"		
	15'-6"		16'-4"		
	16'-0"		16'-10"		
	16'-6"		17'-4"		

