



HOISTWAY PLAN

- 1 TAPE SELECTOR
- 2 LIGHT SWITCH-18" ABOVE LOWEST LANDING (BY OTHERS)
- 3 PIT STOP SWITCH
- 4 PIT LADDER (BY OTHERS)
- 5 SPRING BUFFERS LOCATED ON PIT FLOOR
- 6 LIMIT SWITCH

PLEASE NOTE THAT THESE RAIL REACTION NUMBERS ARE ESTIMATES AND ARE SUBJECT TO CHANGE AS ACCURATE INFORMATION BECOMES AVAILABLE.

SPECIFICATION			
USAGE	PASSENGER		
LOADING CLASS	A		
CAPACITY (LBS.)	3000		
RATED SPEED (FPM)	100,125		
RISE	MAX. 15'-0"		
RAIL REACTION (SEISMIC)			
MAX. RAIL BRKT SPAN	14'-0"		
R1 (LBS.)	1750		
R2 (LBS.)	875		
MAX. RAIL BRKT SPAN (0.5A)	9'-0"		
R1 (LBS.)	1800		
R2 (LBS.)	800		
REV.	DATE	BY	REVISIONS

NOTE:
 FOR APPROVAL
 REVISED FOR APPROVAL
 FINAL DISTRIBUTION
 REVISED FINAL DISTRIBUTION

WHEN THE EQUIPMENT HAS BEEN RELEASED FOR FABRICATION, ANY CHANGES MADE AFTER APPROVAL WILL RESULT IN ADDITIONAL COST AND COMPLETION TIME.

PROJECT: -----
 ADDRESS: -----
 CONTRACTOR: -----
 ARCHITECT: -----
 CONSULTANT: -----
 DRAWN: JC DATE: 9/6/13 APPROVER: JC
 DWG. TITLE: HOISTWAY PLAN & SECTION
 PROJECT NO.: ----- ELEM#: 1
 DRAWING NO.: 101