

	<b>Front Opening</b>	<b>Front and Rear</b>	<b>Front Opening</b>	<b>Front and Rear</b>
Capacity (lbs.)	4000/Service	4000/Service	4500/Service	4500/Service
Speed (fpm)	100, 125, 150	100, 125, 150	100, 125, 150	100, 125, 150
Hoistway (w x d)	7' - 6" x 9' - 1"	7' - 6" x 10' - 1 ¾"	7' - 6" x 9' - 8"	7' - 6" x 10' - 7 ¾"
Platform (w x d)	6' - 0" x 8' - 3"	6' - 0" x 8' - 10 ¾"	6' - 0" x 8' - 10"	6' - 0" x 9' - 4 ¾"
Inside Clear	5' - 8" x 7' - 3 ¾"	5' - 8" x 7' - 4 ¼"	5' - 8" x 7' - 10 ¾"	5' - 8" x 7' - 10 ¼"
Door Type	2S	2S	2S	2S
Entrance Width	4' - 0"	4' - 0"	4' - 0"	4' - 0"
Pit	4' - 0"	4' - 0"	4' - 0"	4' - 0"
Overhead*	12' - 6"	12' - 6"	12' - 6"	12' - 6"
Maximum Travel	50' - 0"	50' - 0"	50' - 0"	50' - 0"
Maximum Number of Stops	6	6	6	6

	<b>Front Opening</b>	<b>Front and Rear</b>	<b>Front Opening</b>	<b>Front and Rear</b>
Capacity (lbs.)	5000/Service	5000/Service	5000/Service	5000/Service
Speed (fpm)	100, 125, 150	100, 125, 150	100, 125, 150	100, 125, 150
Hoistway (w x d)	7' - 6" x 10' - 3"	7' - 6" x 11' - 2 ¾"	8' - 4" x 10' - 3"	8' - 4" x 11' - 2 ¾"
Platform (w x d)	6' - 0" x 9' - 5"	6' - 0" x 9' - 11 ¾"	6' - 4" x 9' - 5"	6' - 4" x 9' - 11 ¾"
Inside Clear	5' - 8" x 8' - 5 ¾"	5' - 8" x 8' - 5 ¼"	6' - 0" x 8' - 5 ¾"	6' - 0" x 8' - 5 ¼"
Door Type	2S	2S	2S	2S
Entrance Width	4' - 0"	4' - 0"	4' - 6"	4' - 6"
Pit	4' - 0"	4' - 0"	4' - 0"	4' - 0"
Overhead*	12' - 6"	12' - 6"	12' - 6"	12' - 6"
Maximum Travel	50' - 0"	50' - 0"	50' - 0"	50' - 0"
Maximum Number of Stops	6	6	6	6

Door Types: 2S: 2 Speed Side, CO: Center Opening, SS: Single Speed Side

*\*Note: The contents of these tables are standard specifications based on an 8 ft. cab height, please consult your local sales office for other specifications.*

*Note that 3" of overhead can be subtracted if no car top guard rails are required.*