

| | Front Opening | Front and Rear | Front Opening | Front and Rear |
|--------------------------------|----------------------|------------------------|----------------------|-----------------------|
| Capacity (lbs.) | 4000/Service | 4000/Service | 4500/Service | 4500/Service |
| Speed (fpm) | 80, 100, 125, 150 | 80, 100, 125, 150 | 80, 100, 125, 150 | 80, 100, 125, 150 |
| Hoistway (w x d) | 8' - 0" x 9' - 2" | 8' - 0" x 10' - 3" | 8' - 0" x 9' - 8" | 8' - 0" x 10' - 9" |
| Platform (w x d) | 6' - 0" x 8' - 4" | 6' - 0" x 8' - 11 1/2" | 6' - 0" x 8' - 10" | 6' - 0" x 9' - 5 1/2" |
| Inside Clear | 5' - 8" x 7' - 6" | 5' - 8" x 7' - 6" | 5' - 8" x 8' - 0" | 5' - 8" x 8' - 0" |
| Door Type | SS, CO | SS, CO | SS, CO | SS, CO |
| Entrance Width | 4' - 0" | 4' - 0" | 4' - 0" | 4' - 0" |
| Pit | 4' - 0" | 4' - 0" | 4' - 0" | 4' - 0" |
| Overhead* | 12' - 6" | 12' - 6" | 12' - 6" | 12' - 6" |
| Maximum Travel | 98' - 0" | 98' - 0" | 98' - 0" | 98' - 0" |
| Maximum Number of Stops | 8 | 8 | 8 | 8 |

| | Front Opening | Front and Rear |
|--|----------------------|------------------------|
| Capacity (lbs.) | 5000/Service | 5000/Service |
| Speed (fpm) | 80, 100, 125, 150 | 80, 100, 125, 150 |
| Hoistway - 4' - 0" opng (w x d) | 8' - 0" x 10' - 2" | 8' - 0" x 11' - 5" |
| Hoistway - 4' - 6" opng (w x d) | 8' - 6" x 10' - 2" | 8' - 6" x 11' - 5" |
| Platform | 6' - 0" x 9' - 4" | 6' - 0" x 10' - 1 1/2" |
| Inside Clear | 5' - 8" x 8' - 8" | 5' - 8" x 8' - 8" |
| Door Type | SS, CO | SS, CO |
| Entrance Width | 4' - 0" or 4' - 6" | 4' - 0" or 4' - 6" |
| Pit | 4' - 0" | 4' - 0" |
| Overhead* | 12' - 6" | 12' - 6" |
| Maximum Travel | 98' - 0" | 98' - 0" |
| Maximum Number of Stops | 8 | 8 |

Door Types: CO: Center Opening, SS: Single Speed Side

**Note: The contents of these tables are standard specifications based on an 8 ft. cab height, please consult your local sales office for other specifications.*