

	Front Opening	Front and Rear	Front Opening	Front and Rear
Capacity (lbs.)	4000/Service	4000/Service	4500/Service	4500/Service
Speed (fpm)	100, 125, 150	100, 125, 150	100, 125, 150	100, 125, 150
Hoistway (w x d)	7' - 8" x 9' - 1"	7' - 8" x 10' - 1 ¾"	7' - 8" x 9' - 8"	7' - 8" x 10' - 7 ¾"
Platform (w x d)	6' - 0" x 8' - 3"	6' - 0" x 8' - 10 ¾"	6' - 0" x 8' - 10"	6' - 0" x 9' - 4 ¾"
Inside Clear	5' - 8" x 7' - 3 ¾"	5' - 8" x 7' - 4 ¼"	5' - 8" x 7' - 10 ¾"	5' - 8" x 7' - 10 ¼"
Door Type	2S	2S	2S	2S
Entrance Width	4' - 0"	4' - 0"	4' - 0"	4' - 0"
Pit	4' - 0"	4' - 0"	4' - 0"	4' - 0"
Overhead*	12' - 10"	12' - 10"	12' - 10"	12' - 10"
Maximum Travel*	12' - 0"	12' - 0"	12' - 0"	12' - 0"
Maximum Number of Stops	2	2	2	2

	Front Opening	Front and Rear	Front Opening	Front and Rear
Capacity (lbs.)	5000/Service	5000/Service	5000/Service	5000/Service
Speed (fpm)	100, 125, 150	100, 125, 150	100, 125, 150	100, 125, 150
Hoistway (w x d)	7' - 8" x 10' - 3"	7' - 8" x 11' - 2 ¾"	8' - 5" x 10' - 3"	8' - 5" x 11' - 2 ¾"
Platform (w x d)	6' - 0" x 9' - 5"	6' - 0" x 9' - 11 ¾"	6' - 4" x 9' - 5"	6' - 4" x 9' - 11 ¾"
Inside Clear	5' - 8" x 8' - 5 ¾"	5' - 8" x 8' - 5 ¼"	6' - 0" x 8' - 5 ¾"	6' - 0" x 8' - 5 ¼"
Door Type	2S	2S	2S	2S
Entrance Width	4' - 0"	4' - 0"	4' - 6"	4' - 6"
Pit	4' - 0"	4' - 0"	4' - 0"	4' - 0"
Overhead*	12' - 10"	12' - 10"	12' - 10"	12' - 10"
Maximum Travel*	12' - 0"	12' - 0"	12' - 0"	12' - 0"
Maximum Number of Stops	2	2	2	2

Door Types: 2S: 2 Speed Side, CO: Center Opening, SS: Single Speed Side

**Note: The contents of these tables are standard specifications based on an 8 ft. cab height with 4'-0" pit and 12'-0" travel or less. Please reference "holeless single stage overhead dimensions" for other arrangement or consult your local sales office for specifications.*