



IDH-S -L2 Hydraulic Passenger Elevators

FRONT ENTRANCE HOLELESS ELEVATORS

STANDARD SPEEDS: 100 FPM AND 125 FPM




Plan View of Center Open Single Slide




Plan View of Handed Single Slide

LEFT HAND SHOWN - RIGHT HAND AVAILABLE



Plan View of Elevator Pit Condition



Composite Hoistway Section

HOLELESS AND SEMI-HOLELESS HOISTWAY DIMENSIONS							
CAPACITY (LBS.)	HOISTWAY		PLATFORM		CAR INSIDE CLEAR		ENTRANCE
	Width	Depth	Width	Depth	Width	Depth	
2100	7' - 6"	5' - 10"	6' - 0"	5' - 1"	5' - 8"	4' - 3"	3' - 0"
2500	8' - 6"	5' - 10"	7' - 0"	5' - 1"	6' - 8"	4' - 3"	3' - 6"
3000	8' - 6"	6' - 3"	7' - 0"	5' - 6"	6' - 8"	4' - 8"	3' - 6"
3500	8' - 6"	6' - 11"	7' - 0"	6' - 2"	6' - 8"	5' - 4"	3' - 6"
4000	9' - 6"	6' - 11"	8' - 0"	6' - 2"	7' - 8"	5' - 4"	4' - 0"

NOTES:

1. Complies with ASME A17.1 code. Confirm dimensions comply with local codes and standards.
2. Provide min. 4" wide divider beam between adjacent hoistways for rail support.
3. For 24" x 84" stretcher use 3500 lbs. min. capacity with handed door or 4000 lbs. with center open door.
4. Provide hoisting beam capable of holding 5000 lb. load. Remove after installation if required.
5. Center opening configuration not available for 2100 lb. capacity elevators.